IN THE CLAIMS

This listing of claims will replace all prior versions and listings of claims in the application:

Listing of Claims:

(previously presented) A method of preparing a potato based food product, the method comprising:

processing potatoes into potato articles having a desired size and shape;

blanching the potato articles;

dipping the blanched potato articles in a solution to prevent non-enzymic oxidation of the potato articles;

drying the dipped potato articles;

coating the potato articles in an emulsion containing starch, oil, salt and colouring to form coated articles;

introducing the coated articles into a hot air environment; and

removing the coated articles from the hot air environment.

- (previously presented) A method as claimed in claim 1, 2. wherein the step of blanching the potato articles comprises immersing the potato articles in a heated water bath at a temperature between 70 °C and 95 °C for between 5 minutes and 20 minutes.
- (previously presented) A method as claimed in claim 1 or claim 2, wherein the step of dipping the blanched potato articles in a solution comprises immersing the potato articles in a sodium acid pyrophosphate solution.

- (previously presented) A method as claimed in claim 3, wherein the sodium acid pyrophosphate solution comprises 1% sodium acid pyrophosphate.
- (previously presented) A method as claimed in claim 3, 5. wherein the sodium acid pyrophosphate solution is provided at a temperature of 65 °C and the potato articles are immersed for a time period of about 60 seconds.
- (previously presented) A method as claimed in claim 1, wherein the step of drying the potato articles comprises introducing the potato articles into an elevated temperature environment.
- 7. (previously presented) A method as claimed in claim 1, wherein the step of drying the dipped potato articles is carried out at ambient temperature.
- (previously presented) A method as claimed in claim 1, wherein the emulsion comprises a mixture including water, oil, starch, colouring, emulsifier, stabilizer and salt.
- (previously presented) A method as claimed in claim 8, 9. wherein the emulsion comprises:

Water	53.00%	_	60.00%
Sunflower Oil	24.00%	-	28.00%
Maize Starch	10.00%	-	12.00%
Turmeric	0.01%	-	0.10%
Liquid Paprika	0.01%	-	0.10%
Emulsifier	0.80%	-	1.00%

Application No.:	10/549,738	Docket No.:	MCCAIN-LTD	3.3-005
------------------	------------	-------------	------------	---------

Gum stabiliser 0.10% - 0.30% Salt 4.00% - 6.00%

10. (previously presented) A method as claimed in claim 1, wherein the emulsion comprises a mixture including water, oil, starch, flour, dextrin, gum, sodium bicarbonate, salt, colouring, oil, sodium acid pyrophosphate and dextrose.

11. (previously presented) A method as claimed in claim 10, wherein the emulsion comprises:

Water	48.00%	_	54.00%
Sunflower oil	13.00%	-	16.00%
Modified Potato Starch	9.00%	_	11.00%
Rice Flour	5.00%	-	7.00%
Potato Dextrin	9.00%	-	11.00%
Maize Starch	4.00%	-	6.00%
Xanthan Gum	0.01%	-	0.10%
Sodium Bicarbonate	0.30%	_	0.40%
Sodium Acid Pyrophosphate	0.40%	-	0.50%
Salt	1.00%	_	2.00%
Turmeric Extract Powder	0.01%	-	0.10%
Paprika Oleoresin	0.01%	_	0.10%
Vegetable Oil	0.01%	-	0.10%
Dextrose	0.30%	-	0.40%
Guar Gum	0.01%	_	0.10%

12. (previously presented) A method as claimed in claim 1, further comprising drying the coated articles prior to introducing the coated articles into the hot air environment.

- (previously presented) A method as claimed in claim 12, wherein the step of drying the coated articles comprises introducing the coated articles into a warm air environment.
- 14. (previously presented) A method as claimed in claim 13, wherein the coated articles are dried at a temperature between 100 °C and 130 °C.
- (previously presented) A method as claimed in claim 14, wherein the coated articles are dried at a temperature between 105 °C and 120 °C.
- (previously presented) A method as claimed in claim 1, wherein the introducing step comprises introducing the coated articles into an impingement oven.
- (previously presented) A method as claimed in claim 1, wherein the hot air environment has a temperature between 240 $^{\circ}$ C and 285 $^{\circ}$ C.
- 18. (cancelled)
- 19. (cancelled)
- 20. (cancelled)
- 21. (cancelled)
- 22. (cancelled)